



throughout the life of the shoes.

safety than the standard, increases the dispersive capacity of the electrostatic charges

## ABOUTBLU/ANATOMIC

CONCRETE

**BALTEUS BLACK** MID

33275 08LA

\$3 SRC **DGUV 112-191** EN ISO 20345:2011

ECO-SOFT

Water repellent and breathable full grain leather with scuff cap.	FEATURES
<b>PLASMAFEEL</b> Lining in 3D fabric that keeps the foot constantly cool and dry thanks to the instantaneous absorption of sweat and its immediate dispersion outside of the shoe. Breathable, antibacterial, resistant to wear and abrasion.	
<i>ECO</i> -SOFT Thermoformed . Runproof , multi -layered , antistatic fabric , that is antibacterial , breathable and absorbent with anti-fungus activated carbons . Shock absorbing heel and plantar arch support. ECO FRIENDLY- RECYCLED MATERIAL	SHOCK ABSORPTION OIL AND IN THE HEEL PYDROCARBONS RESISTANT SOLE TOE CAP
<b>PU/PU DUAL DENSITY BASF PUR Elastopan®</b> polyurethane foam insole, ensures the maximum comfort and the absorption of the impact on all surfaces. Polyurethane outsole, with an elevated grip, resistant to wear, oils and hydrocarbons. System of energy absorption on the heel. It leaves no mark on the surface.	NO MARKING SOLE ANTISTATIC FOOTWEAR BREATHABLE UPPER
The anatomical shape of the injected sole, unlike removable insoles, is inalterable for the entire lifetime of the shoe. The Anatomic sole, following the natural morphology of the foot, provides a natural support to all its points, ensuring maximum comfort	
The <b>POWER CAP</b> is in multilayer fiberglass and rubber particulate. It stands out for its robustness and lightness, guaranteeing a shock absorption up to a max. 200 Joules.Being metal-free is is undetactable by a meta detector, and helps to maintain a constant body temperature. It provides maxmum safety even at extreme temperatures above and below zero, providing a thermal insulation that is better than aluminum or steel toe-caps. It exceeds the EN-ISO 12568 requirements.	WATER-REPELLENT ANTIPERFORMITON TECHNOLOGIES
<b>TEXON ENIGMA ZERO HT2</b> Non-metallic antistatic, flexible, anti-perforation fabric insole, built with several layers of high-tenacity fibres. It ensures perfect thermal insulation Compliant with: EN 12568:2012; EN ISO 20344/345; CSA-Z195-14; ASTM F2413-18	CONTRACTOR OF THE PARTY OF THE
<b>COMPOSHANK</b> Anti-torsion support in ABS. It is applied between the antiperforation midsole and the midsole, corresponding to the arch of the foot. It improves stability on ladders, where foot support is not complete.	(WIC SOL
SILVER STRIP DISCHARGE (SSD) Conductive cotton tape and silver threads inside the upper and in contact with the foot. It is an anti-static device that guarantees greater	12 AMTHERSHITT



UPPER

LINING

INSOLE

SOLE

LAST

**TOE CAP** 

MIDSOLE

SUPPORT

ANTI-STATIC

DEVICE

ANTI-TORSION

WEIGHT SIZE 42 770 gr

Via Egidio Berto, 2 35024 Bovolenta (PD), Italy | T. +39 049 9713211 F. +39 049 5806906 info@panthersafety.it | panthersrl@legalmail.it | www.panthersafety.it

**SIZES** 38-48