



UPPER

Water repellent and breathable Nubuck grain leather with scuff-cap. HI-Tech fabric resistant to tear and abrasion on padded on the back for greater comfort. **SAFETY STRUCTURE**, external reinforcement on the back heel for greater posture stability and high visibility Reflex insert

LINING

**PLASMAFEEL** Lining in 3D fabric that keeps the foot constantly cool and dry thanks to the instantaneous absorption of sweat and its immediate dispersion outside of the shoe. Breathable, antibacterial, resistant to wear and abrasion.

INSOLE

**TERM-SOFT** Thermoformed Needle-tufted felt and aluminium fabric that is antistatic, antibacterial, breathable and absorbent. It isolates against cold and heat. Shock absorbing heel and arch support.

SOLE

**PU/PU DUAL DENSITY BASF PUR Elastopan®** polyurethane foam insole, ensures the maximum comfort and the absorption of the impact on all surfaces. Polyurethane outsole, with an elevated grip, resistant to wear, oils and hydrocarbons. System of energy absorption on the heel. It leaves no mark on the surface.

LAST

The anatomical shape of the injected sole, unlike removable insoles, is inalterable for the entire lifetime of the shoe. The Anatomic sole, following the natural morphology of the foot, provides a natural support to all its points, ensuring maximum comfort

TOE CAP

The **POWER CAP** is in multilayer fiberglass and rubber particulate. It stands out for its robustness and lightness, guaranteeing a shock absorption up to a max. 200 Joules. Being metal-free it is undetectable by a metal detector, and helps to maintain a constant body temperature. It provides maximum safety even at extreme temperatures above and below zero, providing a thermal insulation that is better than aluminum or steel toe-caps. It exceeds the EN-ISO 12568 requirements.

MIDSOLE

**SHIELD-TEX**- Non-metallic antistatic, flexible, anti-perforation fabric insole, built with several layers of high-tensile fibres. Compliant with: EN ISO 20345:2022

ANTI-TORSION  
SUPPORT

**COMPOSHANK** Anti-torsion support in ABS. It is applied between the antiperforation midsole and the midsole, corresponding to the arch of the foot. It improves stability on ladders, where foot support is not complete.

ANTI-STATIC  
DEVICE

**SILVER STRIP DISCHARGE (SSD)** Conductive cotton tape and silver threads inside the upper and in contact with the foot. It is an anti-static device that guarantees greater safety than the standard, increases the dispersive capacity of the electrostatic charges throughout the life of the shoes.


WEIGHT SIZE 42 720 gr

SIZES 38-48

TERM-SOFT



FEATURES



TECHNOLOGIES

