



ABOUTBLU / ANATOMIC

DI-ELECTRIC

VOLTAGE ESR

32275 12LA

**SB E FO P WRU
HRO SRC
DGVU112-191**

EN ISO
20345:2011

CATEGORY II PPE

UPPER Water repellent and breathable full grain waxed leather

LINING **PLASMAFEEL** - Lining in 3D fabric that keeps the foot constantly cool and dry thanks to the instantaneous absorption of sweat and its immediate dispersion outside of the shoe. Breathable, antibacterial, resistant to wear and abrasion.

INSOLE **ISO-TECH** Thermoformed. Runresistant, multi-layered fabric, that is antibacterial, breathable and absorbent with anti-fungus activated carbons. Shock absorbing heel and arch support

OUTSOLE **DI-ELECTRIC PU / Rubber - BASF PUR Elastopan®** polyurethane foam insole, ensures the maximum comfort and the absorption of the impact on all surfaces. Rubber outsole, with an elevated grip, resistant to up to a 300°C (HRO certified), guarantees the maximum levels of slip resistance. Resistant to corrosion by oils and hydrocarbons. It leaves no mark on the surface.

LAST The anatomical shape of the injected sole, unlike removable insoles, is inalterable for the entire lifetime of the shoe. comfort and wellbeing even after a long working day

MIDSOLE **TEXON ENIGMA ZERO HT2** - Non-metallic, flexible, anti-perforation fabric insole, built with several layers of high-tenacity fibres. Compliant with: EN 12568:2012; EN ISO 20344/345; CSA-Z195-14; ASTM F2413-18

TOE CAP The **POWER CAP** is in multilayer fiberglass and rubber particulate. It stands out for its robustness and lightness, guaranteeing a shock absorption up to a max. 200 Joules. Being metal-free is undetectable by a metal detector, and helps to maintain a constant body temperature. It provides maximum safety even at extreme temperatures above and below zero, providing a thermal insulation that is better than aluminium or steel toe caps. It exceeds the EN- ISO12568 requirements

COMPOSHANK Anti-torsion support in ABS. It is applied between the anti-perforation midsole and the midsole, corresponding to the arch of the foot. It improves stability on ladders, where foot support is not complete.

SIZE 38-48

WEIGHT SIZE 42 800 gr

ESR



outsoles certified in accordance with the Canadian CSA Z195-14 standard

FEATURES



TECHNOLOGIES

