



ABOUTBLU / ANATOMIC

DI-ELECTRIC

VOLTAGE ESR

32275 12LA

SB E FO PL WRU HRO SRC
EN ISO 20345:2022+A1:2024
DGVV 112-191
CATEGORY II PPE

UPPER

Water repellent and breathable full grain waxed leather

LINING

PLASMAFEEL - Lining in 3D fabric that keeps the foot constantly cool and dry thanks to the instantaneous absorption of sweat and its immediate dispersion outside of the shoe. Breathable, antibacterial, resistant to wear and abrasion.

INSOLE

ISO-TECH Thermoformed. Runresistant, multi-layered fabric, that is antibacterial, breathable and absorbent with anti-fungus activated carbons. Shock absorbing heel and arch support

OUTSOLE

DI-ELECTRIC PU / Rubber - BASF PUR Elastopan® polyurethane foam insole, ensures the maximum comfort and the absorption of the impact on all surfaces. Rubber outsole, with an elevated grip, resistant to up to a 300°C (HRO certified), guarantees the maximum levels of slip resistance. Resistant to corrosion by oils and hydrocarbons. It leaves no mark on the surface.

LAST

The anatomical shape of the injected sole, unlike removable insoles, is inalterable for the entire lifetime of the shoe. comfort and wellbeing even after a long working day

MIDSOLE

TEXON ENIGMA ZERO HT2 - Non-metallic, flexible, anti-perforation fabric insole, built with several layers of high-tenacity fibers. Compliant with: EN ISO 22568-4:2021; EN ISO 20344; CSA-Z195-14; ASTM F2413-24

TOE CAP

The **POWER CAP** is in multilayer fiberglass and rubber particulate. It stands out for its robustness and lightness, guaranteeing a shock absorption up to a max. 200 Joules. Being metal-free is undetectable by a metal detector, and helps to maintain a constant body temperature. It provides maximum safety even at extreme temperatures above and below zero, providing a thermal insulation that is better than aluminum or steel toe caps. It exceeds the EN ISO 22568-2:2019 requirements

COMPOSHANK

Anti-torsion support in ABS. It is applied between the anti-perforation midsole and the midsole, corresponding to the arch of the foot. It improves stability on ladders, where foot support is not complete.

SIZE

38-48

WEIGHT SIZE 42

800 gr

ESR



outsoles certified in accordance with the Canadian CSA Z195-14 standard

FEATURES



TECHNOLOGIES

