









	ner.	Water-repellent and breathable grain leath	UPPER
FE/	eps the foot constantly cool and dry thanks and its immediate dispersion outside of the o wear and abrasion.		LINING
SHOCK ABSORPTION IN THE HEEL HYI RE	Ilti-layered, antistatic latex-foam fabric, that with anti-fungus activated carbons. Shock		INSOLE
NO MARKING SOLE ANTIS	topan® polyurethane foam insole, ensures of the impact on all surfaces. Polyurethane o wear, oils and hydrocarbons . System of s no mark on the surface .SATRA UK " tance three times greater than standard	the maximum comfort and the absorption outsole, with an elevated grip, resistant to	SOLE
	unlike removable insoles, is inalterable for ic sole, following the natural morphology of s points, ensuring maximum comfort		LAST
ANTIPERFORATION WAT MIDSOLE WAT	The POWER CAP is in multilayer fiberglass and rubber particulate. It stands out for its robustness and lightness, guaranteeing a shock absorption up to a max. 200 Joules.Being metal-free is is undetactable by a meta detector, and helps to maintain a constant body temperature. It provides maxmum safety even at extreme temperatures above and below zero, providing a thermal insulation that is better than aluminum or steel toe-caps. It exceeds the EN-ISO12568 requirements.		TOE CAP
TECH	TEXON ENIGMA ZERO HT2 Non-metallic antistatic, flexible, anti-perforation fabric insole, built with several layers of high-tenacity fibres. It ensures perfect thermal insulation Compliant with: EN 12568:2012; EN ISO 20344/345; CSA-Z195-14; ASTM F2413-18		MIDSOLE
SUP DISHANA	COMPOSHANK Anti-torsion support in ABS. It is applied between the antiperforation midsole and the midsole, corresponding to the arch of the foot. It improves stability on ladders, where foot support is not complete.		ANTI-TORSION SUPPORT
THE SOL			ANTI-STATIC DEVICE
R RANTHERSAFT	SIZES 35-49	IGHT SIZE 42 600 gr	WE



Via Egidio Berto, 2 35024 Bovolenta (PD), Italy | T. +39 049 9713211 F. +39 049 5806906 info@panthersafety.it | panthersrl@legalmail.it | www.panthersafety.it