



ABOUTBLU/ANATOMIC

PROFESSIONAL

## INDIANAPOLIS OCTANE LOW

50351 02LA

S3 ESD SRC DGUV 112-191 EN ISO 20345:2011

**TECH SOFT** 

UPPER	breathable and water-repellent <b>HI-TECH</b> abrasion resistant. Anti-abrasion scuff-cap	fabric with PU reinforcement. tear and	FI	EATURES
LINING	<b>PLASMAFEEL</b> Lining in 3D fabric that kee to the instantaneous absorption of sweat a shoe. Breathable, antibacterial, resistant to	and its immediate dispersion outside of the		
INSOLE	<b>TECH SOFT</b> Thermoformed. Runproof, mu is antibacterial, breathable and absorbent absorbing heel and plantar arch support.		SHOCK ABSORPTION IN THE HEEL	OILAND HYDROCARBONS RESISTANT SOLE  TOE CAP
SOLE	PU / TPU - BASF PUR Elastopan® polyur comfort and the absorption of the impact with an elevated grip, resistant to wear, absorption on the heel.	on all surfaces. Bi-colored TPU outsole,	NO MARKING SOLE AN	TISTATIC FOOTWEAR BREATHABLE UPPER
LAST	The anatomical shape of the injected sole, the entire lifetime of the shoe. The Anatomi the foot, provides a natural support to all its	c sole, following the natural morphology of		
TOE CAP	The <b>POWER CAP</b> is in multilayer fibergles for its robustness and lightness, guarantee Joules. Being metal-free is is undetactable to constant body temperature. It provides may above and below zero, providing a therm or steel toe-caps. It is compliant with CSA ISO12568 requirements.	eing a shock absorption up to a max. 200 by a meta detector, and helps to maintain a strumm safety even at extreme temperatures al insulation that is better than aluminum	METAL FREE	PLUS  AND LADY SIZES  HNOLOGIES
MIDSOLE	<b>TEXON ENIGMA ZERO HT2</b> Non-metallic insole, built with several layers of high-to-insulation Compliant with: EN 12568:2012; F2413-18	enacity fibres. It ensures perfect thermal	Q ASMAFER L	HNOLOGIES CONTRACTOR
ANTI-TORSION SUPPORT	<b>COMPOSHANK</b> Anti-torsion support in ABS. It is applied between the antiperforation midsole and the midsole, corresponding to the arch of the foot. It improves stability on ladders, where foot support is not complete.		ESTROSHAN	STRIP DISCUE
ANTI-STATIC DEVICE	SILVER STRIP DISCHARGE (SSD) Conductive cotton tape and silver threads inside  ANTI-STATIC the upper and in contact with the foot. It is an anti-static device that guarantees greater		THE THE PARTHERS NEEDED	
WEIGHT SIZE 42 520 gr		<b>SIZES</b> 35-49	A PANTHERS NICH	

