



ABOUTBLU/ANATOMIC

WATERPROOF

**ROSSINI**

32374 01LA

S3 WR CI HI HRO SRC

EN ISO 20345:2011

<b>UPPER</b>	Waterproof full grain leather with anti abrasion scuff cap
<b>LINING</b>	waterproof membrane <b>TEPOR®</b> that disperses moisture outside the shoe proportionally to the amount of sweat produced: the more you sweat, the more the membrane activates. Thermo-regulating membrane <b>WINTHERM®</b> that insulates the foot from the cold and heat
<b>INSOLE</b>	<b>HEAT COMFY</b> - Thermoformed. Needle-tufted felt and aluminium fabric that is antibacterial, breathable and absorbent. It isolates against cold and heat, used in CI and HI footwear.
<b>SOLE</b>	<b>PU/RUBBER BASF PUR Elastopan®</b> polyurethane foam insole, ensures the maximum comfort and the absorption of the impact on all surfaces. Polyurethane outsole, with an elevated grip, resistant to up to a <b>300°C (HRO certified)</b> , guarantees the maximum levels of slip resistance. Resistant to corrosion by oils and hydrocarbons. It leaves no mark on the surface.
<b>LAST</b>	The anatomical shape of the injected sole, unlike removable insoles, is inalterable for the entire lifetime of the shoe. The <b>ANATOMIC SOLE</b> , following the natural morphology of the foot, provides a natural support to all its points, ensuring maximum comfort
<b>TOE CAP</b>	The <b>POWER CAP</b> is in multilayer fiberglass and rubber particulate. It stands out for its robustness and lightness, guaranteeing a shock absorption up to a max. 200 Joules. Being metal-free it is undetectable by a metal detector, and helps to maintain a constant body temperature. It provides maximum safety even at extreme temperatures above and below zero, providing a thermal insulation that is better than aluminum or steel toe-caps. It exceeds the EN-ISO12568 requirements.
<b>MIDSOLE</b>	<b>TEXON ENIGMA ZERO HT2</b> Non-metallic antistatic, flexible, anti-perforation fabric insole, built with several layers of high-tenacity fibres. It ensures perfect thermal insulation Compliant with: EN 12568:2012; EN ISO 20344/345; CSA-Z195-14; ASTM F2413-18
<b>ANTI-TORSION SUPPORT</b>	<b>COMPOSHANK</b> Anti-torsion support in ABS. It is applied between the antiperforation midsole and the midsole, corresponding to the arch of the foot. It improves stability on ladders, where foot support is not complete.
<b>ANTI-STATIC DEVICE</b>	<b>SILVER STRIP DISCHARGE (SSD)</b> Conductive cotton tape and silver threads inside the upper and in contact with the foot. It is an anti-static device that guarantees greater safety than the standard, increases the dispersive capacity of the electrostatic charges throughout the life of the shoes.

WEIGHT SIZE 42 760 gr

SIZES 38-48

HEAT COMFY



FEATURES

 SHOCK ABSORPTION IN THE HEEL	 OIL AND HYDROCARBONS RESISTANT SOLE	 TOE CAP
 NO MARKING SOLE	 ANTISTATIC FOOTWEAR	 BREATHABLE UPPER
 WATER-REPELLENT UPPER	 ANTIPERFORATION MIDSOLE	 HRO - HEAT RESISTANT SOLE (300°C)
 CI - COLD INSULATION	 WR - WATERPROOF	 HI-HEAT INSULATION

PLUS

--	--	--

TECHNOLOGIES
