



CONCRETE

SPARTACUS

27309 01LA

S3 SRC EN ISO 20345:2011

FUSSTATIC



UPPER	Water repellent and breathable leather and	l scuff-cap			
LINING	PLASMAFEEL Lining in 3D fabric that kee to the instantaneous absorption of sweat a shoe. Breathable, antibacterial, resistant to	and its immediate dispersion outside of the			
INSOLE	FUSSTATIC Runresistant, multi-layered, a rial, breathable and absorbent. Non-slip on		FEATURES		
SOLE	PU/PU DUAL DENSITY BASF PUR Elast the maximum comfort and the absorption o outsole, with an elevated grip, resistant to energy absorption on the heel. It leaves no	of the impact on all surfaces. Polyurethane o wear, oils and hydrocarbons. System of	SHOCK ABSORPTION IN THE HEEL	OILAND HYDROCARBONS	TOE CAP
TOE CAP	The POWER CAP is in multilayer fiberglass and rubber particulate. It stands out for its robustness and lightness, guaranteeing a shock absorption up to a max. 200 Joules.Being metal-free is is undetactable by a meta detector, and helps to maintain a constant body temperature. It provides maxmum safety even at extreme temperatures above and below zero, providing a thermal insulation that is better than aluminum or steel toe-caps. It exceeds the EN-ISO12568 requirements.			RESISTANT SOLE	BREATHABLE UPPER
MIDSOLE	TEXON ENIGMA ZERO HT2 Non-metallic antistatic, flexible, anti-perforation fabric insole, built with several layers of high-tenacity fibres. It ensures perfect thermal insulation Compliant with: EN 12568:2012; EN ISO 20344/345; CSA-Z195-14; ASTM F2413-18			ANTIPERFORATION MIDSOLE	NETAL FREE
ANTI-TORSION SUPPORT	COMPOSHANK Anti-torsion support in ABS. It is applied between the antiperforation midsole and the midsole, corresponding to the arch of the foot. It improves stability on ladders, where foot support is not complete.		TE Studsmafe		IES
ANTI-STATIC DEVICE					
WEIGHT SIZE 42 590 gr		SIZES 38-48	HE SAT	S-BH	MUTHERSAFETT



Via Egidio Berto, 2 35024 Bovolenta (PD), Italy | T. +39 049 9713211 F. +39 049 5806906 info@panthersafety.it | panthersrl@legalmail.it | www.panthersafety.it