

ABOUTBLU/REGULAR

OIL & GAS

KALAHARI

27310 00LA

S3L FO SR EN ISO 20345:2022



	PER	RFOR	MANC		
	CARATTERISTICHE				
	ASSORBIMENTO				
	DI ENERGIA SUL TALLONE	AGLI IDROC/	OLLE	PUNTALE	
	×	A	X		
	SUOLA ANTITRACCIA	CALZA ANTIS	ITURA IATICA	TOMAIA TRASPIRANTE	
		Á			
	TOMAIA IDROREPELLENTE	LAN ANTIPERF	IINA DRAZIONE		
	PLUS				
		ME			
	TECNOLOGIE				
	Supposed			OWER CRA	
	ST PART OF THE PART	ATT ALL STATE	a number	ASMAFEEL MANA	
Τ+	39 049 9713				

UPPER	Water repellent and breathable full grain leather		
LINING	PLASMAFEEL - Lining in 3D fabric that keeps the foot constantly cool and dry thanks to the instantaneous absorption of sweat and its immediate dispersion outside of the shoe. Breathable, antibacterial, resistant to wear and abrasion.		
INSOLE	PERFORMANCE -Thermoformed. Runresistant, multi-layered, antistatic latex-foan fabric, that is antibacterial, breathable and absorbent with anti-fungus activated car bons. Shock absorbing heel. Non-slip treatment on the reverse side.		
SOLE	PU/PU DUAL DENSITY - BASF PUR Elastopan® polyurethane foam insole, ensures the maximum comfort and the absorption of the impact on all surfaces. Polyurethane outsole, with an elevated grip, resistant to wear, oils and hydrocarbons. System or energy absorption on the heel. It leaves no mark on the surface.		
TOE CAP	The POWER CAP is in multilayer fiberglass and rubber particulate. It stands out for its robustness and lightness, guaranteeing a shock absorption up to a max. 200 Joules.Being metal-free is is undetactable by a meta detector, and helps to maintain a constant body temperature. It provides maxmum safety even at extreme temperatures above and below zero, providing a thermal insulation that is better than aluminum or steel toe-caps. It is compliant with CSA Canada regulations and exceeds the EN-ISO12568 requirements.		
MIDSOLE	TEXON ENIGMA ZERO HT2 Non-metallic antistatic, flexible, anti-perforation fabric insole, built with several layers of high-tenacity fibres. It ensures perfect therma insulation Compliant with: EN 12568:2012; EN ISO 20344/345; CSA-Z195-14; ASTN F2413-18		
ANTI-TORSION SUPPORT	COMPOSHANK Anti-torsion support in ABS. It is applied between the antiperforation midsole and the midsole, corresponding to the arch of the foot. It improves stability on ladders, where foot support is not complete.		
ANTI-STATIC DEVICE	······································		
	IGHT SIZE 42 775 gr	SIZES 38-48	

