



ABOUTBLU/REGULAR

WATERPROOF

STELVIO

30266 01LA









S3 WR CI HI HRO SRC

EN ISO 20345:2011

HEAT COMFY



FEATURES

| | | |
|--|--|--|
|  SHOCK ABSORPTION IN THE HEEL |  OIL AND HYDROCARBONS RESISTANT SOLE |  TOE CAP |
|  NO MARKING SOLE |  ANTISTATIC FOOTWEAR |  BREATHABLE UPPER |
|  WATER-REPELLENT UPPER |  ANTI-PERFORATION MIDSOLE |  HRO- HEAT RESISTANT SOLE (300°C) |
|  HI-HEAT INSULATION |  WR - WATERPROOF |  CI- COLD INSULATION |

PLUS



TECHNOLOGIES



UPPER Water repellent full grain leather and leather scuff-cap. Waterproof

LINING Grain leather with waterproof membrane **TEPOR®** that disperses moisture outside the shoe proportionally to the amount of sweat produced: the more you sweat, the more the membrane activates. Thermo-regulating membrane **WINTHERM®** that insulates the foot from the cold and heat

INSOLE **HEAT COMFY** - Thermoformed. Needle-tufted felt and aluminium fabric that is anti-bacterial, breathable and absorbent. It isolates against cold and heat

SOLE **PU/RUBBER BASF PUR Elastopan®** polyurethane foam insole, ensures the maximum comfort and the absorption of the impact on all surfaces. Polyurethane outsole, with an elevated grip, resistant to up to a **300°C (HRO certified)**, guarantees the maximum levels of slip resistance. Resistant to corrosion by oils and hydrocarbons. It leaves no mark on the surface.

TOE CAP The **POWER CAP** is in multilayer fiberglass and rubber particulate. It stands out for its robustness and lightness, guaranteeing a shock absorption up to a max. 200 Joules. Being metal-free it is undetectable by a meta detector, and helps to maintain a constant body temperature. It provides maximum safety even at extreme temperatures above and below zero, providing a thermal insulation that is better than aluminum or steel toe-caps. It exceeds the EN- ISO12568 requirements.

MIDSOLE **TEXON ENIGMA ZERO HT2** Non-metallic antistatic, flexible, anti-perforation fabric insole, built with several layers of high-tenacity fibres. It ensures perfect thermal insulation Compliant with: EN 12568:2012; EN ISO 20344/345; CSA-Z195-14; ASTM F2413-18

ANTI-TORSION SUPPORT **COMPOSHANK** Anti-torsion support in ABS. It is applied between the antiperforation midsole and the midsole, corresponding to the arch of the foot. It improves stability on ladders, where foot support is not complete.

ANTI-STATIC DEVICE **SILVER STRIP DISCHARGE (SSD)** Conductive cotton tape and silver threads inside the upper and in contact with the foot. It is an anti-static device that guarantees greater safety than the standard, increases the dispersive capacity of the electrostatic charges throughout the life of the shoes.

WEIGHT SIZE 42 740 gr

SIZES 38-48