



ABOUTBLU/ANATOMIC **DI-ELECTRIC SAHARA** ESR 32305 03LA SB E PL FO WPA HRO SC SR EN ISO 20345:2022+A1:2024 CATEGORY II PPE

	ESR CERTIFICATION
Water repellent and breathable full grain waxed leather with KEVLAR stitching	
PLASMAFEEL - Lining in 3D fabric that keeps the foot constantly cool and dry thanks to the instantaneous absorption of sweat and its immediate dispersion outside of the shoe. Breathable, antibacterial, resistant to wear and abrasion.	FEATURES
ISO-TECH - Thermoformed . Runresistant, multi-layered fabric, that is antibacterial, breathable and absorbent with anti-fungus activated carbons. Shock absorbing heel and arch support.	SHOCK ABSORPTION INTHE HEEL INTHE HEEL CARDONS RESISTANT SOLE
PU/RUBBER DIELECTRIC - BASF PUR Elastopan ® polyurethane foam insole, ensures the maximum comfort and the absorption of the impact on all surfaces. Rubber outsole, with an elevated grip, resistant to up to a 300°C (HRO certified) , guarantees the maximum levels of slip resistance. Resistant to corrosion by oils and hydrocarbons. It leaves no mark on the surface.	NO MARKING SOLE WATER-REPELLENT UPPER BREATHABLE UPPER
The anatomical shape of the injected sole, unlike removable insoles, is inalterable for the entire lifetime of the shoe. The ANATOMIC SOLE , following the natural morphology of the foot, provides a natural support to all its points, ensuring maximum comfort	
The POWER CAP is in multilayer fiberglass and rubber particulate. It stands out for its robustness and lightness, guaranteeing a shock absorption up to a max. 200 Joules.Being metal-free is is undetactable by a meta detector, and helps to maintain a constant body temperature. It provides maxmum safety even at extreme temperatures above and below zero, providing a thermal insulation that is better than aluminum or steel toe-caps.	ANTIPERFORATION HRO-HEAT RESISTANT SOLE (300°C) PLUS
TEXON ENIGMA ZERO HT2 Non-metallic flexible, anti-perforation fabric insole, built with several layers of high -tenacity fibres. It ensures perfect thermal insulation Compliant with: EN 12568:2012; EN ISO 20344/345; CSA-Z195-14; ASTM F2413-18	TECHNOLOGIES
COMPOSHANK Anti-torsion support in ABS. It is applied between the antiperforation midsole and the midsole, corresponding to the arch of the foot. It improves stability on ladders, where foot support is not complete.	A CONTRACT OF CONT

Lining	shoe. Breathable, antibacterial, resistant to wear and abrasion.
INSOLE	ISO-TECH - Thermoformed . Runresistant, multi-layered fabric, that is antibacterial, breathable and absorbent with anti-fungus activated carbons. Shock absorbing heel and arch support.
SOLE	PU/RUBBER DIELECTRIC - BASF PUR Elastopan® polyurethane foam insole, ensures the maximum comfort and the absorption of the impact on all surfaces . Rubber outsole, with an elevated grip, resistant to up to a 300°C (HRO certified) , guarantees the maximum levels of slip resistance. Resistant to corrosion by oils and hydrocarbons. It leaves no mark on the surface.
LAST	The anatomical shape of the injected sole, unlike removable insoles, is inalterable for the entire lifetime of the shoe. The ANATOMIC SOLE , following the natural morphology of the foot, provides a natural support to all its points, ensuring maximum comfort
TOE CAP	The POWER CAP is in multilayer fiberglass and rubber particulate. It stands out for its robustness and lightness, guaranteeing a shock absorption up to a max. 200 Joules.Being metal-free is is undetactable by a meta detector, and helps to maintain a constant body temperature. It provides maxmum safety even at extreme temperatures above and below zero, providing a thermal insulation that is better than aluminum or steel toe-caps.
MIDSOLE	TEXON ENIGMA ZERO HT2 Non-metallic flexible, anti-perforation fabric insole, built with several layers of high-tenacity fibres. It ensures perfect thermal insulation Compliant with: EN 12568:2012; EN ISO 20344/345; CSA-Z195-14; ASTM F2413-18
ANTI-TORSION SUPPORT	COMPOSHANK Anti-torsion support in ABS. It is applied between the antiperforation midsole and the midsole, corresponding to the arch of the foot. It improves stability on ladders, where foot support is not complete.

UPPER Water repellent and breathable full grain waxed leather with KEVLAR stitching

WEIGHT SIZE 42 800 gr

SIZES 38-48



LINING

Via Egidio Berto, 2 35024 Bovolenta (PD), Italy | T. +39 049 9713211 F. +39 049 5806906 info@panthersafety.it | panthersrl@legalmail.it | www.panthersafety.it