



ABOUTBLU / ANATOMIC

WATERPROOF

**GALILEO**

32275 11LA

**S3 WR HRO SRC**  
**DGUV 112-191**

**EN ISO 20345:2011**

**UPPER** water repellent full grain leather and HIGH padded collar

**LINING** **WINDTEX®** - Waterproof thermo-regulating membrane: it provides protection from water and wind, maintaining the ideal temperature and humidity between skin and fabric. Elastic, insulating, breathable but with reduced size inside the shoe, it favours the maintenance of a constant temperature throughout the entire body.

**INSOLE** **PERFORMANCE** - Thermoformed. Runresistant, multi-layered, antistatic latex-foam fabric, that is antibacterial, breathable and absorbent with anti-fungus activated carbons. Shock absorbing heel. Non-slip treatment on the reverse side.

**SOLE** **PU/RUBBER BASF PUR Elastopan®** polyurethane foam insole, ensures the maximum comfort and the absorption of the impact on all surfaces. Rubber outsole, with an elevated grip, resistant to up to a **300 °C (HRO certified)**, guarantees the maximum levels of slip resistance. Resistant to corrosion by oils and hydrocarbons. It leaves no mark on the surface.

**LAST** The anatomical shape of the injected sole, unlike removable insoles, is unalterable for the entire lifetime of the shoe. The **ANATOMIC SOLE**, following the natural morphology of the foot, provides a natural support to all its points, ensuring maximum comfort

**TOE CAP** The **POWER CAP** is in multilayer fiberglass and rubber particulate. It stands out for its robustness and lightness, guaranteeing a shock absorption up to a max. 200 Joules. Being metal-free is undetectable by a meta detector, and helps to maintain a constant body temperature. It provides maximum safety even at extreme temperatures above and below zero, providing a thermal insulation that is better than aluminum or steel toe-caps. It exceeds the EN- ISO12568 requirements.

**MIDSOLE** **TEXON ENIGMA ZERO HT2** Non-metallic antistatic, flexible, anti-perforation fabric insole, built with several layers of high-tenacity fibres. It ensures perfect thermal insulation Compliant with: EN 12568:2012; EN ISO 20344/345; CSA-Z195-14; ASTM F2413-18

**ANTI-TORSION SUPPORT** **COMPOSHANK** Anti-torsion support in ABS. It is applied between the antiperforation midsole and the midsole, corresponding to the arch of the foot. It improves stability on ladders, where foot support is not complete.

**ANTI-STATIC DEVICE** **SILVER STRIP DISCHARGE (SSD)** Conductive cotton tape and silver threads inside the upper and in contact with the foot. It is an anti-static device that guarantees greater safety than the standard, increases the dispersive capacity of the electrostatic charges throughout the life of the shoes.

WEIGHT SIZE 42 800 gr

SIZES 38-48

PERFORMANCE



CARATTERISTICHE

 ASSORBIMENTO DI ENERGIA SUL TALLONE	 SUOLA RESISTENTE AGLI OLI E IDROCARBURI	 PUNTALE
 SUOLA ANTIRACCIA	 CALZATURA ANTISTATICA	 TOMAIA TRASPIRANTE
 TOMAIA IDROREPELLENTE	 LAMINA ANTIPERFORAZIONE	 HRO-SUOLA RESISTENTE AL CALORE (300°C)
 WR IMPERMEABILE		

PLUS



TECNOLOGIE

